



Boost Port Adapter

2013-01-02

Thank you for purchasing this ALTA product for your car! Installation of this product should only be performed by persons experienced with installation of aftermarket performance parts and proper operation of high performance vehicles. If vehicle needs to be raised off the ground for installation, the installer must use proper jacks, jack-stands and/or a professional vehicle hoist for safety of the installer and to protect property. If the vehicle is lifted improperly, serious injury or death may occur! Please read through all instructions before performing any portion of installation. If you have any questions, please contact our tech department prior to starting installation. We can be reached in any of the following methods:

Email Tech@ALTAperformance.com

Instant Chat off the main page of www.ALTAperformance.com

Or simply call our tech team at 503-693-1702

GENERAL MODIFICATION NOTE

Modifications to any vehicle can change the handling and performance. As with any vehicle extreme care must be used to prevent loss of control or roll-over during sharp turns or abrupt maneuvers. Always wear seat belts, and drive safely, recognizing that reduced speeds and specialized driving techniques may be required. Failure to drive a vehicle safely may result in serious injury or death. Do not drive a vehicle unless you are familiar with its unique handling characteristics and are confident of your ability to maintain control under all driving conditions. Some modifications (and combinations of modifications) are not recommended and may not be permitted in your state or country. Consult the owner's manual, service manual, instructions accompanying these products, and local laws before purchasing and installing these modifications. You are responsible for the legality and safety of the vehicle you modify using these components.

SPECIAL NOTES:

- Use of the factory service manual can be very helpful during the installation. These can be purchased at the dealership or online. <http://www.realoem.com> has diagrams for the entire car, which can also be helpful.
- The ALTA boost port adapter can be used for getting a boost/vacuum source for gauges, or for adding a Blow-Off Valve.

Parts Included with ALTA BOOST PORT ADAPTER:

- (1) R56 Boost Port
- (1) #12x2.25" sheet metal Screw
- (1) 1/8th NPT 3/32 Barb



OEM MAP sensor located behind intake on the manifold

ALTA Boost Port Installation

- 1) Remove intake system, and locate Manifold pressure sensor. Remove screw securing MAP sensor to manifold.
- 2) Install ALTA boost port into manifold making sure that o-ring goes in nice and smooth. Lubricating o-ring help installation go smoother.

- 3) Install OEM MAP sensor into ALTA Boost port, and secure to manifold using supplied screw. Be careful not to tighten screw too much.
- 4) Install Vacuum hose to port on side of ALTA Boost Port, and connect to gauge or Blow-off-valve.

Questions, Comments and Suggestions Contact: Tech@ALTAperformance.com
Visit Our Website for Instant Chat Options at <http://www.ALTAperformance.com>
Call Our Tech Team at 503-693-1702